

ELFA



LOW PRESSURE PAINT TRANSFER PUMPS

The range is suitable for transferring paint materials, oils, explosive liquids, feed multiple spray guns and paint circulation systems. It is designed for high delivery upto 120 ltr/min. and more.



FEATURES

- Pneumatically sensed Air Motor
- High Flow Rate - Four Ball Pump
- Stainless Steel rust proof Hydraulic Body
- Easy Maintenance
- Ice Free Air Motors
- Non turbulent flow suitable for metallic and water borne paints

TECHNICAL SPECIFICATIONS

Type	2.4000	2.6500	3.2000	2.2000
*Ratio	2:1	2:1	3:1	2:1
Output per Cycle	4000 cc	6500 cc	2000 cc	2000 cc
Air Motor Piston Ø	250 mm	250 mm	200 mm	160 mm
Stroke Length	120 mm	200 mm	120 mm	120 mm
Transfer Volume @ 20 cycles/min	80 ltr	130 ltr	40 ltr	40 ltr
Air Inlet Pressure Max.	6 bar	6 bar	6 bar	6 bar
Output Pressure Max.	12 bar	12 bar	18 bar	12 bar
Air Consumption N ltr / min Max. @ 20 cycles	1650	2750	1060	680

*Other Higher ratios request



J -138, MIDC Bhosari, Pune - 411 026. INDIA.
Tel.: +91 (020) 30781022 / 27130331 **Fax :** +91 (020) 30781051
E-mail.: sales@vrcoatings.com • vrcoatings@eth.net • **Web :** www.vrcoatings.com