

HIPPO

LOW PRESSURE PAINT TRANSFER PUMPS



VR Coatings Pvt. Ltd.
Providing Solutions....



FEATURES

- Pneumatically sensed stall free Air Motor
- High Flow Rate
- Stainless Steel rust proof Hydraulic Body
- Easy Maintenance
- Ice Free Motors
- Light and Easy to handle
- Compliance to EC Norms



TECHNICAL SPECIFICATIONS

Type	1:170	12:400	3:900	5:900
*Ratio	1:1	12:1	3:1	5:1
Output per Cycle (th)	170cc	400 cc	900 cc	900 cc
Air Motor Piston ϕ	-	80 mm	125 mm	160 mm
Stroke Length	120 mm	120 mm	120 mm	120 mm
Recommended Transfer volume @15 cycles per min.	4.25 ltr	10 ltr	22.5 ltr	22.5 ltr
Air Inlet Pressure (th)	6 bar	6 bar	6 bar	6 bar
Output Pressure Max (th)	6 bar	72 bar	18 bar	30 bar
Air Consumption N ltr/min @15 cycles		127	309	507
CFM at 6 bar & 15 cycles		4.4	10.91	17.91

*Other ratios on request

*Actual pump may vary with catalogue images as per technical specifications.

The range is suitable for transferring paint materials, explosive liquids, feed multiple spray guns and paint circulation systems. It is designed for high delivery upto 30 ltr/min.

